



TRUCK & BUS TIRES CATALOG



Email: sales@staridge.com
Website: www.suretractires.com

WWW.SURETRACTIRES.COM

CONTENTS

6.50R16LT	01	235/75R17.5	14
7.00R16LT	01	245/70R17.5	15
7.50R16LT	02	225/70R19.5	15
8.25R16LT	02	245/70R19.5	16
8.25R20LT	03	265/70R19.5	16
9.00R20	03	285/70R19.5	17
10.00R20	04	285/75R24.5	17
11.00R20	04	255/70R22.5	18
12.00R20	05	275/70R22.5	18
12.00R24	05	275/80R22.5	19
8R22.5	06	295/60R22.5	19
9R22.5	06	295/75R22.5	20
10R22.5	06	295/80R22.5	21
11R22.5	07	315/60R22.5	23
11R24.5	09	305/70R22.5	23
12R22.5	11	315/70R22.5	24
13R22.5	12	315/80R22.5	25
9.5R17.5	12	385/55R22.5	27
215/70R17.5	13	385/65R22.5	27
215/75R17.5	13	425/65R22.5	28
225/80R17.5	14	445/65R22.5	28

6.50R16LT



RT518

RT562

RT568

RT277

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	12	110/105	K	10.0	143.5	ALL POSITION
RT562	12	110/105	L	10.5	146.0	ALL POSITION
RT568	12	110/105	L	10.5	146.0	ALL POSITION
RT277	12	110/105	K	10.0	148.0	STEER

7.00R16LT



RT562

RT568

RT518

RT378

RT277

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	14	118/114	L	11.5	160.0	ALL POSITION
RT568	14	118/114	L	11.0	154.0	ALL POSITION
RT518	14	118/114	L	11.0	157.0	ALL POSITION
RT378	14	118/114	L	14.0	160.0	DRIVE
RT277	14	118/114	L	11.5	160.0	STEER

7.50R16LT



RT518

RT562

RT568

RT337

RT378

RT277

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	14	122/118	L	13.0	160.0	ALL POSITION
RT562	14	122/118	L	12.5	170.0	ALL POSITION
RT568	14	122/118	L	12.5	170.0	ALL POSITION
RT337	16	125/121	D	16.5	174.0	DRIVE
RT378	14	122/118	L	15.0	174.0	DRIVE
RT277	16	125/121	L	13.0	160.0	STEER

8.25R16LT



RT518

RT568

RT337

RT378

RT377

RT277

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	16	128/124	K	14.0	178.0	ALL POSITION
RT568	16	128/124	L	13.0	180.0	ALL POSITION
RT337	16	132/128	D	20.0	184.0	DRIVE
RT378	16	128/124	L	15.0	184.0	DRIVE
RT377	16	128/124	F	17.5	180.0	DRIVE
RT277	18	132/128	K	14.0	178.0	STEER

8.25R20LT



RT518

RT568

RT378

RT377

RT391

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	16	139/137	K	14.0	180.0	ALL POSITION
RT568	16	139/137	K	14.0	180.0	ALL POSITION
RT378	16	139/137	K	15.0	184.0	DRIVE
RT377	16	139/137	F	17.5	184.0	DRIVE
RT391	16	139/137	K	15.0	184.0	DRIVE

9.00R20



RT518

RT568

RT377

RT378

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	16	144/142	K	15.5	195.0	ALL POSITION
RT568	16	144/142	K	15.0	195.0	ALL POSITION
RT377	16	144/142	D	22.5	210.0	DRIVE
RT378	16	144/142	K	16.0	200.0	DRIVE

10.00R20



RT518

RT568

RT337

RT378

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	18	149/146	K	16.0	209.0	ALL POSITION
RT568	18	149/146	K	15.0	210.0	ALL POSITION
RT337	18	149/146	D	23.0	218.0	DRIVE
RT378	18	149/146	K	19.5	214.0	DRIVE

11.00R20



RT277

RT518

RT568

RT378

RT391

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT277	18	152/149	K	16.5	232.0	ALL POSITION
RT518	18	152/149	K	17.0	223.0	ALL POSITION
RT568	18	152/149	K	16.0	226.0	DRIVE
RT378	18	152/149	K	18.5	230.0	DRIVE
RT391	18	152/149	K	20.0	238.0	DRIVE

12.00R20



RT277 RT518 RT568 RT337



RT317+ RT378 RT391 RT387

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT277	20	156/153	K	16.5	244.0	STEER
RT518	20	156/153	K	17.5	238.0	ALL POSITION
RT568	20	156/153	K	16.5	236.0	ALL POSITION
RT337	20	156/153	G	24.0	240.0	DRIVE
RT317+	20	156/153	G	23.0	242.0	DRIVE
RT378	20	156/153	K	19.0	242.0	DRIVE
RT391	20	156/153	K	20.5	248.0	DRIVE
RT387	20	156/153	M	22.0	242.0	DRIVE

12.00R24



RT518 RT568

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT518	20	160/157	K	17.5	238.0	ALL POSITION
RT568	20	160/157	K	16.5	236.0	ALL POSITION

8R22.5



RT562

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	14	130/128	L	13.0	166.0	ALL POSITION

9R22.5



RT562

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	14	136/134	L	14.0	180.0	ALL POSITION

10R22.5



RT562

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	16	144/142	L	14.0	200.0	ALL POSITION

IIR22.5



RT256+ GUIDE MAX RT256 RT277 S601+



RT803 RT807 RT369 FORCE MAX D691+



RT518 RT568 RT538 RT301+ RT367



RT366 RT365 RT317 RT316 RT318



RT318S RT338S RT339S RT361 RT371

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256+	16	146/143	M	15.0	226.0	STEER
GUIDE MAX	18	149/146	M	16.5	232.0	STEER
RT256	16	146/143	M	15.5	220.0	STEER
RT277	18	149/146	L	15.5	230.0	STEER
S601+	16	146/143	M	15.0	206.0	STEER
RT803	16	144/142	M	11.0	226.0	TRAILER
RT807	16	146/143	M	10.5	220.0	TRAILER
RT369	16	146/143	L	23.0	226.0	DRIVE
FORCE MAX	18	149/146	L	23.0	240.0	DRIVE
D691+	16	146/143	M	20.5	208.0	DRIVE
RT518	16	146/143	L	17.0	216.0	ALL POSITION
RT568	16	146/143	M	16.0	220.0	ALL POSITION
RT538	16	146/143	J	16.5	220.0	ALL POSITION
RT301+	16	148/145	L	23.0	226.0	DRIVE
RT367	16	146/143	M	23.0	226.0	DRIVE
RT366	16	146/143	L	23.0	230.0	DRIVE
RT365	16	146/143	M	21.0	208.0	DRIVE
RT317	18	149/146	G	23.0	224.0	DRIVE
RT316	16	146/143	M	18.0	224.0	DRIVE
RT318	16	146/143	K	21.0	228.0	SNOW
RT318S	16	146/143	K	21.0	230.0	SNOW
RT338S	16	146/143	K	21.0	230.0	SNOW
RT339S	16	146/143	M	21.0	226.0	SNOW
RT361	16	146/143	M	23.8	246.0	ALL SEASON
RT371	16	146/143	K	25.0	220.0	FORESTRY



IIR24.5



RT256+ RT256 S601+ RT518 RT568



RT369 D691+ RT367 RT366 RT365



RT317 RT371 RT361 RT318S RT338S



RT339S GUIDE MAX FORCE MAX

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256+	16	149/146	M	15.0	226.0	STEER
RT256	16	149/146	L	15.5	220.0	STEER
GUIDE MAX	16	149/146	M	16.5	236.0	STEER
S601+	16	149/146	M	15.0	206.0	STEER
RT518	16	149/146	L	17.0	226.0	ALL POSITION
RT568	16	149/146	L	16.0	220.0	ALL POSITION
FORCE MAX	16	149/146	L	23.5	240.0	DRIVE
RT369	16	149/146	L	23.0	226.0	DRIVE
D691+	16	149/146	M	20.5	208.0	DRIVE
RT367	16	149/146	L	23.0	226.0	DRIVE
RT366	16	149/146	K	23.0	230.0	DRIVE
RT365	16	149/146	K	20.5	215.0	DRIVE
RT317	16	149/146	G	21.0	224.0	DRIVE
RT371	16	149/146	K	25.0	220.0	FORESTRY
RT361	16	149/146	K	22.0	244.0	ALL SEASON
RT318S	16	149/146	K	21.0	230.0	SNOW
RT338S	16	149/146	K	21.0	230.0	SNOW
RT339S	16	149/146	K	21.0	226.0	SNOW

12R22.5



RT277

RT256

RT518

RT568



RT806

RT301+

RT317+

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT277	18	152/149	L	18.0	240.0	STEER
RT256	18	152/149	L	16.5	230.0	STEER
RT518	18	152/149	L	17.0	240.0	ALL POSITION
RT568	18	152/149	L	18.0	240.0	ALL POSITION
RT806	18	152/149	M	15.0	230.0	ALL POSITION
RT301+	18	152/149	L	23.0	242.0	DRIVE
RT317+	18	152/149	J	24.0	240.0	DRIVE

13R22.5



RT277

RT256

RT518

RT568

RT558

RT349

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT277	20	156/153	K	17.0	250.0	STEER
RT256	18	154/151	L	15.0	254.0	STEER
RT518	20	154/151	K	17.5	242.0	ALL POSITION
RT568	18	154/151	K	17.0	242.0	ALL POSITION
RT558	18	154/151	K	21.0	242.0	DRIVE
RT349	18	154/151	L	21.0	254.0	DRIVE

9.5R17.5



RT256

RT568

RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	133/131	L	14.0	182.0	STEER
RT568	16	131/129	L	13.0	182.0	ALL POSITION
RT302	18	143/141	J	15.5	182.0	DRIVE

215/70R17.5



RT562

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	14	123/121	L	12.0	170.0	ALL POSITION

215/75R17.5



RT256 L258 RT562 RT301+ L359 RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	127/124	L	12.0	185.0	STEER
L258	16	127/124	L	10.0	165.0	STEER
RT562	16	135/133	J	13.0	185.0	ALL POSITION
RT301+	16	135/133	J	16.0	185.0	DRIVE
L359	16	127/124	L	13.0	165.0	DRIVE
RT302	18	135/133	J	15.5	185.0	DRIVE

225/80R17.5



RT256 RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	123/122	L	13.0	185.0	STEER
RT302	18	123/122	L	14.0	185.0	DRIVE

235/75R17.5



RT256 L258 RT562 RT319 L359 RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	132/129	L	13.0	192.0	STEER
L258	16	132/129	L	10.0	180.0	STEER
RT562	16	143/141	J	13.0	192.0	ALL POSITION
RT319	16	143/141	J	16.0	192.0	DRIVE
L359	16	132/129	L	13.0	180.0	DRIVE
RT302	18	143/141	J	15.5	192.0	DRIVE

245/70R17.5



RT562

RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	14	134/132	L	14.0	208.0	ALL POSITION
RT302	18	134/132	K	15.5	208.0	DRIVE

225/70R19.5



RT562

RT316

RT302

RT305A

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	16	130/128	L	14.0	186.0	ALL POSITION
RT316	14	128/126	M	15.0	161.0	DRIVE
RT302	18	132/130	K	15.5	186.0	DRIVE
RT305A	16	132/130	K	16.0	186.0	DRIVE

245/70R19.5



RT256

RT562

RT316

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	135/133	L	14.0	208.0	STEER
RT562	18	141/140	J	14.0	198.0	ALL POSITION
RT316	14	136/134	L	15.0	204.0	DRIVE

265/70R19.5



RT256

RT562

RT316

RT302

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	143/141	J	14.0	215.0	STEER
RT562	16	140/138	L	14.0	210.0	ALL POSITION
RT316	16	140/138	L	15.5	212.0	DRIVE
RT302	18	143/141	J	16.0	215.0	DRIVE

285/70R19.5



RT562

RT316

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT562	16	146/144	L	14.0	224.0	ALL POSITION
RT316	18	150/148	J	16.5	230.0	DRIVE

255/70R22.5



RT256

RT286

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	140/137	L	13.0	216.0	STEER
RT286	16	140/137	M	12.5	196.0	ALL POSITION

285/75R24.5



RT256+

RT256

RT369

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256+	16	147/144	M	15.0	224.0	STEER
RT256	16	147/144	M	15.0	216.0	STEER
RT369	16	147/144	L	23.0	232.0	DRIVE

275/70R22.5



RT256

RT538

RT316

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	16	146/143	L	15.0	230.0	STEER
RT538	16	148/145	J	16.5	236.0	ALL POSITION
RT316	16	148/145	M	18.5	240.0	DRIVE

275/80R22.5



RT256

RT349

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	149/146	L	15.0	230.0	ALL POSITION
RT349	18	152/149	M	17.0	230.0	DRIVE

295/60R22.5



RT256

RT316

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	150/147	L	16.0	240.0	ALL POSITION
RT316	18	150/147	M	20.0	254.0	DRIVE

295/75R22.5



RT256+

RT256

S601+

RT803

GUIDE MAX



FORCE MAX

RT369

D691+

RT318S

RT338S

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
GUIDE MAX	16	149/146	M	16.5	240.0	STEER
RT256+	16	146/143	M	15.0	230.0	STEER
RT256	16	146/143	M	15.0	234.0	STEER
S601+	16	146/143	L	15.0	210.0	STEER
RT803	16	144/141	M	11.0	230.0	TRAILER
FORCE MAX	16	149/146	L	23.5	245.0	DRIVE
RT369	16	146/143	L	23.0	238.0	DRIVE
D691+	16	147/144	L	20.0	215.0	DRIVE
RT318S	16	146/143	K	23.0	234.0	SNOW
RT338S	16	146/143	K	23.0	234.0	SNOW

295/80R22.5



RT277 RT256 RT258 RT236 L258



RT518 RT568 RT266 RT276 RT377



RT317+ RT301+ RT316 RT558+ RT353



RT349 L359 L528 L327

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT277	18	152/149	L	16.0	256.0	STEER
RT256	18	152/149	L	15.5	240.0	STEER
RT258	18	152/149	M	17.5	240.0	STEER
RT236	18	152/149	M	16.0	232.0	STEER
L258	18	152/149	L	14.5	220.0	STEER
RT518	18	152/149	L	16.0	236.0	ALL POSITION
RT568	18	152/149	L	16.0	240.0	ALL POSITION
RT266	18	152/149	F	18.0	248.0	DRIVE
RT276	18	152/149	F	22.0	248.0	DRIVE
RT377	18	152/149	K	19.0	246.0	DRIVE
RT317+	18	152/149	J	22.0	256.0	DRIVE
RT301+	18	152/149	L	23.0	242.0	DRIVE
RT316	18	152/149	M	19.0	248.0	DRIVE
RT558+	18	152/149	K	21.0	256.0	DRIVE
RT353	18	152/149	K	22.0	260.0	DRIVE
RT349	18	152/149	M	18.0	248.0	DRIVE
L359	18	152/149	L	19.5	225.0	DRIVE
L528	18	152/149	L	19.5	225.0	DRIVE
L327	18	152/149	L	21.0	225.0	DRIVE

315/60R22.5



RT256

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	152/148	M	15.0	270.0	STEER

315/70R22.5



RT256

RT316

RT359

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	18	154/150	M	15.0	260.0	STEER
RT316	18	154/150	M	19.0	264.0	DRIVE
RT359	20	154/151	L	21.0	280.0	DRIVE

305/70R22.5



RT538

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT538	20	152/150	L	18.0	305.0	ALL POSITION



315/80R22.5



PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	20	157/154	L	15.0	252.0	STEER
RT277	20	157/154	L	16.0	262.0	STEER
L529	20	157/154	L	14.5	228.0	STEER
L258	20	157/154	L	14.0	228.0	STEER
RT518	20	157/154	K	15.0	235.0	ALL POSITION
L518	20	157/154	L	14.5	228.0	ALL POSITION
RT568	18	157/154	M	22.0	242.0	ALL POSITION
RT348	20	157/154	K	22.0	246.0	DRIVE
RT349	20	157/154	K	22.0	258.0	DRIVE
RT353	20	157/154	K	22.0	270.0	DRIVE
RT558	20	157/154	K	20.5	242.0	DRIVE
RT558+	20	157/154	K	22.0	270.0	DRIVE
RT317+	20	157/154	K	22.0	270.0	DRIVE
L359	20	157/154	L	19.5	230.0	DRIVE
L528	20	157/154	L	19.5	230.0	DRIVE
RT316	18	157/154	M	19.0	260.0	DRIVE
RT302	20	157/154	K	20.0	246.0	DRIVE
RT359	22	160/157	K	21.0	270.0	DRIVE
RT319	18	154/151	M	24.0	280.0	SNOW

385/55R22.5



RT216

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT216	20	164	K	15.0	320.0	ALL POSITION

425/65R22.5



RT216

RT306

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT216	20	164	K	16.0	332.0	ALL POSITION
RT306	20	165	K	18.0	332.0	DRIVE

385/65R22.5



RT256

RT277

RT216

RT805

RT306

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT256	20	160	L	15.0	286.0	STEER
RT277	20	160	K	16.5	310.0	STEER
RT216	20	160	L	16.0	286.0	ALL POSITION
RT805	20	164	K	16.7	286.0	ALL POSITION
RT306	20	164	K	17.0	290.0	DRIVE

445/65R22.5



RT216

RT306

PATTERN	PR	LOAD INDEX	SPEED RATING	TREAD DEPTH(mm)	TREAD WIDTH(mm)	RECOMMEND POSITION
RT216	20	169	K	15.0	360.0	ALL POSITION
RT306	20	169	K	18.0	360.0	DRIVE